



## 100mm Rear Entry SS Case Overview

### Features

- Suitable for hydraulic oil and gaseous media that do not corrode any copper base alloy
- Available in nominal sizes 63 and 100
- Thread form: BSP (G1/4 and G1/2), NPT (1/4NPT and 1/2NPT)
- Housing made of Stainless Steel (1.4301)
- Sight glass made of Acrylic
- Glycerine filled
- U-bolt or flange mounting kit on request

Pressure Range	Units (secondary units)	Fitting	Fitting Material
-1 to 3	Bar (PSI)	1/2" BSPP	Brass
0 to 6	Bar (PSI)	1/2" BSPP	Brass
0 to 10	Bar (PSI)	1/2" BSPP	Brass
0 to 16	Bar (PSI)	1/2" BSPP	Brass
0 to 25	Bar (PSI)	1/2" BSPP	Brass
0 to 40	Bar (PSI)	1/2" BSPP	Brass
0 to 60	Bar (PSI)	1/2" BSPP	Brass
0 to 80	Bar (PSI)	1/2" BSPP	Brass
0 to 100	Bar (PSI)	1/2" BSPP	Brass
0 to 160	Bar (PSI)	1/2" BSPP	Brass
0 to 250	Bar (PSI)	1/2" BSPP	Brass
0 to 315	Bar (PSI)	1/2" BSPP	Brass
0 to 400	Bar (PSI)	1/2" BSPP	Brass
0 to 600	Bar (PSI)	1/2" BSPP	Brass
0 to 700	Bar (PSI)	1/2" BSPP	Brass